Power Harrow - Technical Specifications

Model	Speed	L x W x H (mm)	Working Width (mm/inch)	HP / Kw	No. of Blades	(Kg/lbs)
SRP-75	Single	1014 x 869 x 1210	750 / 29.53	35+/26+	6	400/880
SRP-100	Single/Multi	1014 x 1120 x 1210	1000 / 39.37	45+/34+	8	460/1012
SRP-125	Multi	1014 x 1365 x 1210	1250 / 49.21	55+/41+	10	500/1100
SRP-150	Multi	1014 x 1610 x 1210	1500 / 59.06	60+/45+	12	545/1199
SRP-175	Multi	1014 x 1855 x 1210	1750 / 68.9	65+/48+	14	590/1298
SRP-200	Multi	1014 x 2100 x 1210	2000 / 78.74	70+/52+	16	640/1408
SRP-225	Multi	1014 x 2345 x 1210	2250 / 88.58	75+/56+	18	680/1496
SRP-250	Multi	1014 x 2590 x 1210	2500 / 98.43	80+/60+	20	720/1584
SRP-275	Multi	1014 x 2835 x 1210	2750 / 108.3	85+/63+	22	760/1672
SRP-300	Multi	1014 x 3080 x 1210	3000 / 118.1	90+/67+	24	800/1760

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

Optional



Universal joint power transmission shaft with clutch





Roller	Roller Dia (mm / inch)	Teeth Length (mm / inch)
PACKER	421 /16.58	64.5 / 2.54
SPIKE	515 / 20.28	167 / 6.58
CAGE	383 / 15 08	NΔ

Features



Swinging brackets



Universal joint power transmission shaft with shear bolt torque limiter



Multi speed gearbox for 540 & 1000 RPM PTO



Single speed gear box for 540 RPM PTO



Rear leveling bar with pin or screw adjustment



Blades with 12 mm thickness and 285 mm length made of boron steel material



Floating side plates

Accessories shown in the pictures may not be part of standard fitment.



Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat- INDIA, Pin – 360311 Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270537, Fax: + 91 (2827) 270457. Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Correspondence: Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.







Power Harrow

Shaktiman Power Harrow is suitable for the crops which require deeper tillage like Potato and tuber crops. Its boron steel long blades help achieve deep tillage in any type of soil. It reduces the number of tillage operations reducing number of passes, thus help in reducing compaction of soil. It comes with option of multispeed to adjust speed as per the customer's requirements. The leveling bar is a standard feature and accessories consist of three types of Rollers: Packer Roller, Spike Roller & Cage Roller





Advantages...

- Its long and sharp blades can easily plough any land and achieve tillage depth up to 10 inches.
- Its sturdy structure is welded with high thickness plates which makes sure that it operates under toughest conditions.
- Its Gear Box designed with quality components promises longer life cycle of the implement.
- It ensures faster operation and completes function in less time reducing fuel consumption and soil compaction.